

Screw type auxiliary take-ups are the most common take-ups used on models 138VP, 196VP, 138LR, 196LR, 196CALR, 196ZPA and 251CALR for additional belt take-up. Live roller model ATS4 shown at left and ATS6 shown below.

## SPECIFY MODEL NUMBER PER EXAMPLE

#### ATS4-33-R

ATS(pulley diameter\*)-(between frames)-(live roller type)

\*Specify 4 for model ATS4 with 4" dia. pulleys or 6 for model ATS6 with 6" dia. pulleys.



#### **SPECIFICATIONS**

**PULLEY:** (2) 4" dia. with 1-3/16" dia. shaft, crowned, for model ATS4; (2) 6" dia. with 1-7/16" dia. shaft, crowned, for model ATS6.

**FRAME:** 7" x 1-1/2" x 12 ga. steel.

**TAKE-UP:** 24" belt take-up.

**BEARINGS:** Heavy duty, relubable, ball bearings with cast iron housings.

#### **MODEL ATS4 FOR LIVE ROLLERS**

	15"						
WT.	105	113	117	125	129	141	153

#### **MODEL ATS6 FOR LIVE ROLLERS**

BF	15"	19"	21"	25"	27"	33"	39"
WT.	15" 119	129	135	146	151	167	183

■ 24 hour shipment ■ 2 week shipment

# **SCREW TYPE AUXILIARY TAKE-UP (FOR BELT CONVEYORS)**





strew type described by a strewty of the most common take-ups used for models 250TB, 350SB, 350BSB, 350BOS, 196RB, 196RBF, 350SBF and 251RB for additional belt take-up. Belt conveyor model ATS4 shown at left and ATS6 shown above.

#### SPECIFY MODEL NUMBER PER EXAMPLE

#### ATS6-21-B

ATS(pulley diameter\*)-(between frames)-(belt conveyor type\*\*)

\*Specify 4 for model ATS4 with 4" dia. pulleys or 6 for model ATS6 with 6" dia. pulleys.

\*\*When attaching to 250TB or 350BOS, BF dimension = belt width + 1".

NOTE: 24 hour shipment on 45" and 51" BF does not include models 250TB or 350BOS.

#### **SPECIFICATIONS**

**PULLEY:** (2) 4" dia. with 1-3/16" dia. shaft, crowned, for model ATS4; (2) 6" dia. with 1-7/16" dia. shaft, crowned, for model ATS6.

**FRAME:** 7" x 1-1/2" x 12 ga. steel.

TAKE-UP: 24" belt take-up.

**BEARINGS:** Heavy duty, relubable, ball bearings with cast iron housings.



#### **MODEL ATS4 FOR BELT CONV.**

Belt	6"	12"	18"	24"	30"	36"	42"	48"
BF	9"	15"	21"	27"	33"	39"	45"	51"
WT.	122	134	146	158	170	182	194	

### MODEL ATS6 FOR BELT CONV.

Belt	6"	12"	18"	24"	30"	36"	42"	48"
BF	9"	15"	21"	27"	33"	39"	45"	51"
WT.	132	148	164	180	196	212	228	244

■ 24 hour shipment ■ 2 week shipment