PRODUCT STOPS ANGLE AND ROLLER STOPS

Model ASM Angle stop

Both angle and roller stops serve as an economical means to stopping goods at a given fixed point. "BR" brackets or angle stop quickly attaches to conveyor frame top flange.

SPECIFICATIONS

ANGLE STOP: Model ASL for light duty and ASM for medium duty applications (1-1/2" x 1-1/2" x 10 ga.); Model ASH for heavy duty applications (1-1/2" x 1-1/2" x 7 ga.).

ROLLER STOP: Includes pair of brackets and roller as specified in model number.

BUTT END STOPS

WIDTHS: Medium and heavy duty 24 hour shipments include 13", 15", 17", 19", 21", 23", 25", 27", 31", 33", 37", 39", 43", 45", 47" and 51" BF; light duty available in 12", 18" and 24" OAW.

ANGLE STOPS MODEL NUMBER

ASM-33

AS (light, medium or heavy duty*)-(between frames**) *Specify L for light duty, M for medium duty or H for heavy duty.

**Specify OAW for model ASL, available in 12", 18" and 24" OAW only and is suited specifically for wheel conveyors and 138 gravity series.

ROLLER STOPS MODEL NUMBER

BR-(roller type*)-(between frames) *Specify 138G, 196S, 196G, 192S, 199S, 254S, 251S or 297S.



24 hour shipment



SPECIFICATIONS

CONSTRUCTION: 12 ga. for model BSL; 10 ga. for BSM; 7 ga. for BSH.

FRAME SIZE: Model BSL for 2.5" frame height ONLY; model BSM for 3.5", 4" and 4.5"; model BSH for 4" and 5" frame heights. **HEIGHT:** Designed to extend 1.5" above top of frame.



BUTT END STOPS MODEL NUMBER

BSH-1.5-4-51

BS (light, medium, heavy or extra heavy duty*)-(height above frame)-(frame size)-(between frames@) *Specify L for light duty, M for medium duty or H for heavy duty.

@Specify 12", 18" or 24" overall width for model BSL light duty butt end stop.

WIDTHS: Model BSM and BSH widths include 13", 15", 17", 19", 21", 23", 25", 27", 31", 33", 37", 39", 43", 45", 47" and 51" BF; BSL available in 12", 18" and 24" OAW only.